

# UNIVERSAL TILE FLASHING

## Overview

Quarrix Universal Tile Flashing is the all-in-one defender against water damage and roof leaks on pitched roofs. A fully adhered, expandable aluminum flashing, with an 11-3/4" width that provides continuous protection on all roof-to-wall applications. This flashing easily contours to the shape of the roof and adheres to most roofing materials including asphalt, clay, concrete, steel and composite roof tile. Designed with a unique butyl backing that provides a weather-tight seal on the following roof applications: headwall, chimney, hip, ridge, gable end, skylight or pipe stack.



## Quarrix Universal Tile Flashing Benefits

- Universal**  
 Easy to bend material suitable for all composite tile, asphalt shingles, clay and slate profile applications.
- Durable**  
 UV-resistant aluminum surface paired with a complete peel and stick butyl backing.
- Architectural Appeal**  
 Available in four colors to match any roofing material. This all-in-one flashing also provides a weather-tight seal anywhere you need to protect against weather intrusion.
- Complete System**  
 Quarrix created the System Advantage™, a line of high-quality roofing components that combat water drainage and poor air circulation in water shedding tile roofs. This full line of roofing accessories include: Tile Fasteners, Tile Battens, Universal Tile Flashing, Universal Tile Ridge Vent and more.

### AVAILABLE COLORS



## UNIVERSAL TILE FLASHING SPECIFICATIONS

Part #	Color	Width	Length	Pitches	Weather Blocking Material	Adhesive
226490	Black	11-3/4"	16'	3/12 to 20/12	Durable UV-resistant Aluminum	High-temperature butyl adhesive with synthetic release liner - can be applied in 40°F to 150°F
227289	Terra Cotta	11-3/4"				
227290	Venetian Red	11-3/4"				
227291	Brown	11-3/4"				

SS-UTF10-1.1.18